



The screen shots look different because I am using a newer version. Functionality is the same.

Mavix Configurator- Update Firmware

Manual Update | Unit Auto Update | Multi Unit Auto Update | Ping

Connect to:

IP: 72 54 151 106

User: administrator

Password: []

MediaRacer

1XX 100X

Unit firmware version

Bios: [] Checksum []

Software: []

Codec: []

Read

Manual Update

status.txt

Checksum : 0576B8EE

C:\Documents and Settings\Administrator\Desktop\status.txt

Get

Edit

Put

Verify

FTP

Select status.txt and click on GET and EDIT



Network Your Surveillance

```
status - Notepad
File Edit Format View Help
System Module Id : 0xF (RS232)
Debug Switch : 0x3
FPGA Revision : 0x2
vxworks Version : Vxworks5.5.1
BSP Version : 1.2/30
BIOS SW Version : 7.1.0.3t- v2 - May 26 2008, 17:51:48
APP SW Version : 7.1.0.3t- v2 - May 26 2008, 17:49:36
Codec Name : Mpeg4 7.1.0.3
Codec Version : Major = 2, Minor = 1
Unit Mode : Application

***** System Settings *****
Create Defaults : 0

MAC Address : 00:03:A3:01:21:F9
Serial Number : 022806080180
NVRam Saved RTC : FRI MAY 30 14:54:44 2008
Real-Time Clock(lcl): FRI MAY 30 14:55:44 2008
Real-Time Clock(gmt): FRI MAY 30 12:55:44 2008
Console Port : 3
Console Baud : 38400
Startup Delay : 3
Remote Boot wait : 20
Boot Device : flash
Boot FileName : /flash0/vxworks.bin
Target Name : MediaRacer
Other : motfec
Flags : 0x0

***** Network Settings *****
Network Phy Mode : Auto-Negotiation, 100Mbit/s, Full-Duplex, Link up
Network Driver Mode : Auto-Negotiation, 100Mbit/s, Full-Duplex
Network Startup Mode: 3 (auto-negotiation)
LAN IP : 72.54.151.106
```

This line shows current console port. You can either change it to 1 or disable it by inserting 0.